

SAFETY DATA SHEET

1. Identification

Product Identifier: CUSTOM CLS METAL PARTS PROTECTOR

Other means of identification

SDS number: RE1000036116

Recommended restrictions

Product use: Coating

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Custom CLS LLC
Address: 1101 ELSINORE PLACE
Chester, PA 19013
Telephone: 484-483-7530
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Germ Cell Mutagenicity Category 1B

Carcinogenicity Category 1A

Specific Target Organ Toxicity -
Repeated Exposure Category 1¹.

Aspiration Hazard Category 1

Target Organs

1. Nervous System

Environmental Hazards

Acute hazards to the aquatic
environment Category 3

Label Elements

Hazard Symbol:



Signal Word:

Danger

Hazard Statement:	Extremely flammable aerosol. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.
Response:	IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%) [*]
Butane	106-97-8	20 - <50%
Stoddard solvent	8052-41-3	20 - <50%
Naphtha (petroleum), light alkylate	64741-66-8	10 - <25%
Propane	74-98-6	10 - <20%
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	1 - <5%
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	1 - <5%
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	64742-54-7	1 - <5%
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	1 - <5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

**Conditions for safe storage,
including any
incompatibilities:**

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended (03 2016)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Stoddard solvent	TWA	100 ppm 525 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Mist.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Distillates (petroleum), hydrotreated light paraffinic - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)

Distillates (petroleum), hydrotreated light paraffinic - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2014)
Distillates (petroleum), solvent-dewaxed light paraffinic - Mist.	STEL	10 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	REL	5 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Distillates (petroleum), solvent-dewaxed light paraffinic - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2010)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: Spray Aerosol
Color: No data available.

Odor: No data available.

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): Estimated 9.5 %(V)

Flammability limit - lower (%): Estimated 1.9 %(V)

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: Estimated 3,102 - 4,481 hPa (20 °C)

Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-Ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.
-----------------	--

Specified substance(s):

Naphtha (petroleum),
light alkylate

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum),
hydrotreated light
paraffinic

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed light paraffinic	LD 50 (Rat): > 5,000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	LD 50 (Rat): > 5,000 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD 50 (Rat): > 5,000 mg/kg
Dermal	
Product:	Not classified for acute toxicity based on available data.
Specified substance(s):	
Naphtha (petroleum), light alkylate	LD 50 (Rabbit): > 6,000 mg/kg
Distillates (petroleum), hydrotreated light paraffinic	LD 50 (Rabbit): > 5,000 mg/kg
Distillates (petroleum), solvent-dewaxed light paraffinic	LD 50 (Rabbit): > 5,000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	LD 50 (Rabbit): > 5,000 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD 50 (Rabbit): > 2,000 mg/kg
Inhalation	
Product:	ATEmix: 13.39 mg/l
Repeated dose toxicity	
Product:	No data available.
Specified substance(s):	
Butane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Naphtha (petroleum), light alkylate	NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Distillates (petroleum), hydrotreated light paraffinic	NOAEL (Rabbit(Female, Male), Dermal): 1,000 mg/kg Dermal Experimental result, Key study
Distillates (petroleum), solvent-dewaxed light paraffinic	NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation Experimental result, Key study LOAEL (Rat(Male), Oral, 13 Weeks): 125 mg/kg Oral Read-across from supporting substance (structural analogue or surrogate), Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): >= 2,000 mg/kg Dermal Experimental result, Key study

Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation Experimental result, Key study LOAEL (Mouse(Male), Dermal, 24 Months): 100 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): >= 2,000 mg/kg Dermal Experimental result, Key study
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NOAEL (Rat, Inhalation): 500 mg/m3 Inhalation Experimental result, Supporting study NOAEL : 100 mg/m3 Inhalation Read-across from supporting substance (structural analogue or surrogate), Supporting study NOAEL : 5 mg/m3 Inhalation Read-across from supporting substance (structural analogue or surrogate), Supporting study NOAEL (Rat, Inhalation): > 1,500 mg/m3 Inhalation Experimental result, Supporting study LOAEL (Rat(Male), Oral, 13 Weeks): 125 mg/kg Oral Read-across from supporting substance (structural analogue or surrogate), Key study

Skin Corrosion/Irritation

Product:

No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	In vitro (Human): not corrosive Experimental result, Supporting study
Distillates (petroleum), hydrotreated light paraffinic	in vivo (Rabbit): Not irritant Experimental result, Key study
Distillates (petroleum), solvent-dewaxed light paraffinic	in vivo (Rabbit): Not irritant Experimental result, Key study
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	in vivo (Rabbit): Not irritant Experimental result, Key study
Distillates (petroleum), solvent-dewaxed heavy paraffinic	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product:

No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	Rabbit, 24 - 72 hrs: Not irritating
Distillates (petroleum), hydrotreated light paraffinic	Rabbit, 48 hrs: Not irritating
Distillates (petroleum), solvent-dewaxed light paraffinic	Rabbit, 48 hrs: Not irritating
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	Rabbit, 48 hrs: Not irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit, 48 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Distillates (petroleum), hydrotreated light paraffinic	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Distillates (petroleum), solvent-dewaxed light paraffinic	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Distillates (petroleum), hydrotreated light paraffinic	Overall evaluation: 3. Not classifiable as to carcinogenicity to humans.
Distillates (petroleum), solvent-dewaxed light paraffinic	Overall evaluation: 3. Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: Nervous System - Causes damage to organs.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):

Stoddard solvent	Nervous System - Category 1
------------------	-----------------------------

Target Organs

Specific Target Organ Toxicity - Repeated Exposure: Nervous System

Aspiration Hazard

Product: No data available.

Specified substance(s):

Stoddard solvent May be fatal if swallowed and enters airways.
Naphtha (petroleum), light alkylate May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Naphtha (petroleum), light alkylate LL 50 (Oncorhynchus mykiss, 96 h): 10 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Distillates (petroleum), hydrotreated light paraffinic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed light paraffinic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed heavy paraffinic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Naphtha (petroleum), light alkylate EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated light paraffinic EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed light paraffinic EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed heavy paraffinic	EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study
---	---

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting study
Distillates (petroleum), solvent-dewaxed light paraffinic	NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study
Distillates (petroleum), solvent-dewaxed light paraffinic	NOAEL (Daphnia magna): 10 mg/l Experimental result, Key study
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	NOAEL (Daphnia magna): >= 1,000 mg/l Experimental result, Supporting study
Distillates (petroleum), solvent-dewaxed heavy paraffinic	EC 50 (Daphnia magna): > 1,000 mg/l Experimental result, Supporting study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Naphtha (petroleum), light alkylate	77.05 % Detected in water. Experimental result, Supporting study 90.35 % (28 d) Detected in water. Experimental result, Supporting study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Distillates (petroleum), hydrotreated light paraffinic	31 % (28 d) Detected in water. Experimental result, Supporting study

Distillates (petroleum), solvent-dewaxed light paraffinic	31 % (28 d) Detected in water. Experimental result, Supporting study 2 - 8 % (28 d) Detected in water. Experimental result, Supporting study
---	---

Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	2 - 8 % (28 d) Detected in water. Experimental result, Supporting study 31 % (28 d) Detected in water. Experimental result, Supporting study
---	---

Distillates (petroleum), solvent-dewaxed heavy paraffinic	2 - 8 % (28 d) Detected in water. Experimental result, Supporting study 31 % (28 d) Detected in water. Read-across based on grouping of substances (category approach), Supporting study
---	---

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
-------------------------------------	--

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Butane	No data available.
Stoddard solvent	No data available.
Naphtha (petroleum), light alkylate	No data available.
Propane	No data available.
Distillates (petroleum), hydrotreated light paraffinic	No data available.
Distillates (petroleum), solvent-dewaxed light paraffinic	No data available.
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	No data available.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	-
Packing Group:	II
Marine Pollutant:	No
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	—
EmS No.:	
Packing Group:	—
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

15. Regulatory information**US Federal Regulations**

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Propane	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Delayed (Chronic) Health Hazard
- Immediate (Acute) Health Hazards
- Flammable aerosol
- Germ Cell Mutagenicity
- Carcinogenicity
- Specific Target Organ Toxicity - Repeated Exposure
- Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Stoddard solvent		

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Stoddard solvent	
Propane	lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Butane	10000 lbs
Stoddard solvent	10000 lbs
Naphtha (petroleum), light alkylate	10000 lbs
Propane	10000 lbs
Distillates (petroleum), hydrotreated light paraffinic	10000 lbs
Distillates (petroleum), solvent-dewaxed light paraffinic	10000 lbs
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO	10000 lbs
Distillates (petroleum), solvent-dewaxed heavy paraffinic	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations**US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Butane
Stoddard solvent
Propane
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO
Distillates (petroleum), solvent-dewaxed heavy paraffinic
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed light paraffinic

US. Massachusetts RTK - Substance List

<u>Chemical Identity</u>
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed light paraffinic

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u>
Butane
Stoddard solvent
Propane
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO
Distillates (petroleum), solvent-dewaxed heavy paraffinic
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed light paraffinic

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations**Montreal protocol**

Stoddard solvent

Stockholm convention

Stoddard solvent

Rotterdam convention
Stoddard solvent

Kyoto protocol

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 04/30/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.