

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

SECTION 1: Product and company identification

Product name : XtreamX Dry Silicon Lube & Release Agent
Use of the substance/mixture : Lubricant
Product code : 8102
Company : CUSTOM CLS
4009 Market St. Unit. N.
Upper Chichester PA, PA 19014 - US
T 484-483-7830
Emergency number : 484-483-7830

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification
Flam. Aerosol 1 H222
Eye Irrit. 2A H319
Repr. 2 H361
STOT SE 3 H336
Asp. Tox. 1 H304

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)



GHS02

GHS07

GHS08

Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Extremely flammable aerosol.
May be fatal if swallowed and enters airways.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing gas.
Wash thoroughly after handling
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye protection, face protection.
If swallowed: Immediately call a doctor, a POISON CENTER.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Call a doctor, a POISON CENTER if you feel unwell.
Do NOT induce vomiting.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container to comply with local/regional/national/international regulations..

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

Name	Product identifier	%	GHS-US classification
Acetone (Solvent)	(CAS-No.) 67-64-1	20 – 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Butane (Propellant gas (Aerosol))	(CAS-No.) 106-97-8	20 – 40	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Propane (Propellant gas (Aerosol))	(CAS-No.) 74-98-6	20 – 40	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Heptane (Solvent)	(CAS-No.) 142-82-5	2.5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Solvent Naphtha (Petroleum), Light Aliphatic (Solvent)	(CAS-No.) 64742-89-8	2.5 – 10	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Cyclohexane (Solvent)	(CAS-No.) 110-82-7	1 – 2.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Hexane (Solvent)	(CAS-No.) 110-54-3	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene (Solvent)	(CAS-No.) 108-88-3	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Take off immediately all contaminated clothing. show this sheet where possible. Wash contaminated clothing before reuse.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Immediately call a POISON CENTER/doctor. Rinse mouth. Do not induce vomiting. Vomiting: prevent asphyxia/aspiration pneumonia.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes serious eye irritation. Irritation to throat. May be fatal if swallowed and enters airways.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness. Headache. Nausea. Fatigue. Irritation of the nasal mucous membranes.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation. Redness of the eye tissue.
- Symptoms/effects after ingestion : Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Keep watching the victim. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

Suitable extinguishing media : Alcohol-resistant foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Contents under pressure. Pressurised container: May burst if heated.
Reactivity : Thermal decomposition may produce : hazardous gases.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air. May accumulate in low areas e.g. close to the ground. No flames, no sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.
Emergency procedures : Do not breathe gas. Do not touch spilled material. Ventilate spillage area. Advise local authorities if considered necessary.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Prevent soil and water pollution. Avoid release to the environment. Stop leak if safe to do so. Advise local authorities if considered necessary.

6.3. Methods and material for containment and cleaning up

For containment : Keep combustibles (wood, paper, oil, etc.) away from spilled material. Eliminate every possible source of ignition. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Prevent the product from entering drains or confined areas.
Methods for cleaning up : Take up liquid spill into inert absorbent material. Following product recovery, flush area with water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use. Do not use if spray button is missing or defective.
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use only non-sparking tools. Use only explosion-free electrical equipment with earth. Avoid contact during pregnancy/while nursing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Observe normal hygiene standards. Do not re-use empty containers. Avoid prolonged and repeated contact with skin. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Avoid breathing gas. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing.
Hygiene measures : Wash contaminated clothing before reuse. Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge.
Storage conditions : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Refrigerate.
Incompatible products : Refer to Section 10 on Incompatible Materials.
Storage area : Aerosol 3.
Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

8.1. Control parameters

Acetone (67-64-1)

ACGIH	ACGIH OEL TWA [ppm]	250 ppm
ACGIH	ACGIH OEL STEL [ppm]	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
OSHA	OSHA PEL TWA [1]	2400 mg/m ³
OSHA	OSHA PEL TWA [2]	1000 ppm

Butane (106-97-8)

ACGIH	ACGIH OEL TWA [ppm]	1000 ppm
-------	---------------------	----------

Propane (74-98-6)

ACGIH	ACGIH OEL TWA [ppm]	1000 ppm
ACGIH	Remark (ACGIH)	Simple Asphyxiant
OSHA	OSHA PEL TWA [1]	1800 mg/m ³
OSHA	OSHA PEL TWA [2]	1000 ppm

Heptane (142-82-5)

OSHA	OSHA PEL TWA [1]	2000 mg/m ³
OSHA	OSHA PEL TWA [2]	500 ppm

Solvent Naphtha (Petroleum), Light Aliphatic (64742-89-8)

Not applicable

Cyclohexane (110-82-7)

ACGIH	ACGIH OEL TWA [ppm]	100 ppm
ACGIH	Remark (ACGIH)	CNS impair
OSHA	OSHA PEL TWA [1]	1050 mg/m ³
OSHA	OSHA PEL TWA [2]	300 ppm

Hexane (110-54-3)

ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	Remark (ACGIH)	CNS impair; peripheral neuropathy; eye irr; Skin; BEI
OSHA	OSHA PEL TWA [1]	1800 mg/m ³
OSHA	OSHA PEL TWA [2]	500 ppm

Toluene (108-88-3)

ACGIH	ACGIH OEL TWA [ppm]	20 ppm
ACGIH	Remark (ACGIH)	Visual impair; female repro; pregnancy loss; A4; BEI
OSHA	OSHA PEL TWA [2]	200 ppm
OSHA	OSHA PEL C [ppm]	300 ppm

8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Provide sufficient air exchange and/or exhaust. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. . If exposure limits have not been established, maintain airborne levels to an acceptable level. . Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

: Gloves. Protective clothing. Protective goggles. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



Hand protection

: Gloves.

Eye protection

: Safety glasses.

Skin and body protection

: Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

Respiratory protection	: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazard protection	: Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Consumer exposure controls	: When using do not smoke. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use good personal hygiene practices. Take off contaminated clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol, Clear, colorless liquid
Odour	: solvent odor
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 150.86 °F estimated
Flash point	: -156 °F propellant estimated
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20°C	: No data available
Density	: 0.759 – 0.769 g/ml estimated
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: 232.86 °C estimated
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce : hazardous gases.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. No flames, no sparks. Eliminate all sources of ignition. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

Cyclohexane (110-82-7)

LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

LC50 Inhalation - Rat	> 32.88 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
-----------------------	--

Hexane (110-54-3)	
LD50 oral rat	16000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 3350 mg/kg bodyweight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 17.6 mg/l air (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE CLP (oral)	16000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Headache. Nausea. Fatigue. Irritation of the nasal mucous membranes.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness of the eye tissue.
Symptoms/effects after ingestion	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 12: Ecological information

12.1. Toxicity

Cyclohexane (110-82-7)	
LC50 - Fish [1]	4.5 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	0.9 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

Cyclohexane (110-82-7)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O ₂ /g substance

Hexane (110-54-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	3.52 g O ₂ /g substance

12.3. Bioaccumulative potential

Cyclohexane (110-82-7)	
BCF - Fish [1]	167 l/kg (Pimephales promelas, QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Hexane (110-54-3)	
BCF - Fish [1]	501.187 (Pimephales promelas, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with local/regional/national regulations. Do not allow into drains or water courses.
- Product/Packaging disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.
- Additional information : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Handle empty containers with care because residual vapours are flammable. Handle uncleaned empty containers as full ones. Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

- Transport document description (DOT) : UN1950 Aerosols flammable, (each not exceeding 1 L capacity), 2.1
- UN-No.(DOT) : UN1950
- Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)
- Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- Marine pollutant : Yes (IMDG only)



- DOT Packaging Non Bulk (49 CFR 173.xxx) : None
- DOT Packaging Bulk (49 CFR 173.xxx) : None
- DOT Special Provisions (49 CFR 172.102) : N82
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
- DOT Vessel Stowage Location : A
- DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

- Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

- UN-No. (IMDG) : UN1950
- Proper Shipping Name (IMDG) : Aerosols
- Class (IMDG) : 2.1 - Flammable gases

Air transport

- UN-No. (IATA) : UN1950
- Proper Shipping Name (IATA) : Aerosols, flammable
- Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

XtreamX Dry Silicon Lube & Release Agent

Safety Data Sheet

Acetone	(67-64-1)	CERCLA RQ5000 lb
Cyclohexane	(110-82-7)	CERCLA RQ1000 lb
Hexane	(110-54-3)	CERCLA RQ5000 lb
Toluene	(108-88-3)	CERCLA RQ1000 lb


WARNING

This product can expose you to n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.